

输入交流电抗器 Input AC Reactor

380V输入交流电抗器(2%压降)选型表
380V Input AC Reactor (2% drop) Selection Table

| 电抗器型号<br>Reactor Type                                                            | 图号<br>Picture NO. | 功率<br>Power ( KW ) | 额定<br>电流<br>Rated Current (A) | 绝缘<br>等级<br>Insulation Class | 重量<br>(kg)<br>Weight (kg) | 尺 寸<br>Dimension(±5mm) |     |     |     |     |     |     |     |    |     |        |    | 铜排尺寸<br>Terminal Size |         |    |       |  |  |
|----------------------------------------------------------------------------------|-------------------|--------------------|-------------------------------|------------------------------|---------------------------|------------------------|-----|-----|-----|-----|-----|-----|-----|----|-----|--------|----|-----------------------|---------|----|-------|--|--|
|                                                                                  |                   |                    |                               |                              |                           | D                      | D1  | D2  | W   | W1  | W2  | H   | H1  | H2 | E   | A*B    | A  | A1                    | B       | T  | C     |  |  |
|                                                                                  |                   |                    |                               |                              |                           |                        |     |     |     |     |     |     |     |    |     |        |    |                       |         |    |       |  |  |
| ACL-0005-EISC-E3M8B                                                              | 图 A<br>Picture A  | 1.5                | 5                             | F                            | 2.48                      | 110                    | 91  | 105 | /   | 65  | 84  | 130 | /   | /  | /   | 6*11   |    |                       | 町洋      |    |       |  |  |
| ACL-0007-EISC-E2M5B                                                              |                   | 2.2                | 7                             | F                            | 2.58                      | 110                    | 91  | 105 | /   | 65  | 84  | 130 | /   | /  | /   | 6*11   |    |                       | 町洋      |    |       |  |  |
| ACL-0010-EISC-E1M5B                                                              |                   | 3.7                | 10                            | F                            | 2.67                      | 110                    | 91  | 105 | /   | 65  | 84  | 130 | /   | /  | /   | 6*11   |    |                       | 町洋      |    |       |  |  |
| ACL-0015-EISH-E1M0B                                                              |                   | 5.5                | 15                            | F                            | 3.45                      | 155                    | 95  | 148 | /   | 61  | 76  | 150 | /   | /  | /   | 6*15   |    |                       | 町洋      |    |       |  |  |
| ACL-0020-EISH-EM75B                                                              |                   | 7.5                | 20                            | F                            | 3.25                      | 155                    | 95  | 148 | /   | 61  | 76  | 150 | /   | /  | /   | 6*15   |    |                       | 町洋      |    |       |  |  |
| ACL-0030-EISH-EM60B                                                              | 图 B<br>Picture B  | 11                 | 30                            | F                            | 5.13                      | 155                    | 95  | 148 | 150 | 80  | 95  | 130 | /   | /  | /   | 6*15   |    |                       | KF 8-5  |    |       |  |  |
| ACL-0040-EISH-EM42B                                                              |                   | 15                 | 40                            | F                            | 5.2                       | 155                    | 95  | 148 | 150 | 80  | 95  | 130 | /   | /  | /   | 6*15   |    |                       | KF 8-5  |    |       |  |  |
| ACL-0050-EISH-EM35B                                                              |                   | 18.5               | 50                            | F                            | 6.91                      | 195                    | 120 | 188 | 130 | 72  | 92  | 160 | /   | /  | /   | 8.5*20 |    |                       | KF 14-6 |    |       |  |  |
| ACL-0060-EISH-EM28B                                                              |                   | 22                 | 60                            | F                            | 7.28                      | 195                    | 120 | 188 | 135 | 72  | 92  | 160 | /   | /  | /   | 8.5*20 |    |                       | KF 22-6 |    |       |  |  |
| ACL-0080-EISC-EM19B                                                              |                   | 30                 | 80                            | F                            | 7.55                      | 195                    | 120 | 188 | 150 | 72  | 92  | 160 | /   | /  | /   | 8.5*20 |    |                       | KF 22-6 |    |       |  |  |
| ACL-0090-EISC-EM19B                                                              |                   | 37                 | 90                            | F                            | 7.55                      | 195                    | 120 | 188 | 150 | 72  | 92  | 160 | /   | /  | /   | 8.5*20 |    |                       | KF 22-6 |    |       |  |  |
| ACL-0120-EISC-EM13B                                                              |                   | 45                 | 120                           | F                            | 10.44                     | 195                    | 120 | 188 | 135 | 92  | 112 | 160 | 75  | 40 | 78  | 8.5*20 | 20 | /                     | 10      | 4  | φ9    |  |  |
| 备注: 公差 D:max D1:±1 D2:±1 W:max W1:±2 W2:±2 H:max H1:±5 H2:±5 E:±10,其余未注公差±0.5mm. |                   |                    |                               |                              |                           |                        |     |     |     |     |     |     |     |    |     |        |    |                       |         |    |       |  |  |
| ACL-0150-EISH-EM11B                                                              | 图 C<br>Picture C  | 55                 | 150                           | F                            | 14.8                      | 250                    | 182 | 81  | 155 | 76  | 102 | 228 | 140 | 45 | 92  | 11*18  | 25 | /                     | 13      | 5  | φ11   |  |  |
| ACL-0200-EISH-E80UB                                                              |                   | 75                 | 200                           | F                            | 19.2                      | 250                    | 182 | 81  | 175 | 96  | 122 | 228 | 140 | 40 | 102 | 11*18  | 25 | /                     | 13      | 5  | φ11   |  |  |
| ACL-0250-EISH-E65UB                                                              |                   | 110                | 250                           | F                            | 22.1                      | 250                    | 182 | 81  | 175 | 96  | 122 | 260 | 155 | 50 | 102 | 11*18  | 25 | /                     | 13      | 5  | φ11   |  |  |
| ACL-0290-EISH-E50UB                                                              |                   | 132                | 290                           | F                            | 28.3                      | 290                    | 214 | 95  | 180 | 100 | 126 | 270 | 155 | 54 | 107 | 11*18  | 30 | /                     | 15      | 5  | φ12   |  |  |
| ACL-0330-EISH-E50UB                                                              |                   | 160                | 330                           | F                            | 28.3                      | 290                    | 214 | 95  | 180 | 100 | 126 | 270 | 155 | 60 | 107 | 11*18  | 30 | /                     | 15      | 5  | φ12   |  |  |
| ACL-0390-EISH-E44UB                                                              |                   | 185                | 390                           | F                            | 31.8                      | 320                    | 243 | 106 | 190 | 112 | 142 | 270 | 155 | 52 | 107 | 12*20  | 30 | /                     | 15      | 5  | φ12   |  |  |
| ACL-0490-EISH-E35UB                                                              |                   | 220                | 490                           | F                            | 43.6                      | 320                    | 243 | 106 | 220 | 122 | 152 | 305 | 190 | 60 | 137 | 12*20  | 50 | 22                    | 23      | 8  | 2-φ12 |  |  |
| ACL-0530-EISH-E35UB                                                              |                   | 240                | 530                           | F                            | 43.6                      | 320                    | 243 | 106 | 220 | 122 | 152 | 305 | 190 | 52 | 137 | 12*20  | 50 | 22                    | 23      | 8  | 2-φ12 |  |  |
| ACL-0600-EISH-E25UB                                                              |                   | 280                | 600                           | F                            | 52                        | 320                    | 243 | 106 | 240 | 137 | 167 | 305 | 195 | 50 | 145 | 12*20  | 50 | 22                    | 23      | 8  | 2-φ12 |  |  |
| ACL-0660-EISH-E25UB                                                              |                   | 300                | 660                           | F                            | 52                        | 320                    | 243 | 106 | 240 | 137 | 167 | 305 | 195 | 50 | 145 | 12*20  | 50 | 22                    | 23      | 8  | 2-φ12 |  |  |
| ACL-0800-EISH-E25UB                                                              | 图 D<br>Picture D  | 380                | 800                           | F                            | 68.5                      | 385                    | 260 | 123 | 250 | 175 | 198 | 390 | 230 | 70 | 142 | 12*20  | 50 | 22                    | 23      | 8  | 2-φ12 |  |  |
| ACL-1000-EISH-E14UB                                                              |                   | 450                | 1000                          | F                            | 68.5                      | 385                    | 260 | 123 | 250 | 175 | 198 | 390 | 230 | 70 | 142 | 12*20  | 50 | 22                    | 23      | 8  | 2-φ12 |  |  |
| ACL-1250-EISH-E11UB                                                              |                   | 550                | 1250                          | F                            | 106                       | 395                    | 275 | 130 | 325 | 175 | 198 | 430 | 280 | 65 | 215 | 12*20  | 60 | 26                    | 27      | 12 | 4-φ12 |  |  |
| ACL-1600-EISH-E12UB                                                              |                   | 630                | 1600                          | F                            | 110                       | 395                    | 275 | 130 | 330 | 175 | 198 | 430 | 280 | 65 | 215 | 12*20  | 60 | 26                    | 27      | 12 | 4-φ12 |  |  |

备注: (1): Picture C公差 D: max D1: ±1 D2: ±5 W: max W1: ±2 W2: ±2 H: max H1: ±5 H2: ±5 E: ±10, 其余未注公差±0.5mm. (以上参数仅供参考, 选型时请咨询我司业务)  
Picture D公差 D: max D1: ±2 D2: ±5 W: max W1: ±1 W2: ±1 H: max H1: ±5 H2: ±5 E: ±10, 其余未注公差±0.5mm.  
(2): 以上型号为我司标准品, 其它规格可以根据客户要求定制  
(3): H级产品可以根据客户要求定制。

产品尺寸图 (Product Size)

